

Manufacturer of the Week



This week our Manufacturer of the Week is ILP. Enjoy 15% off the products featured in this catalog.



code: MOTWILP

TABLE OF CONTENT

| OW Series Open Face Wall Pack | 3 |
|---|----|
| VS New Generation Value Strip LED Fixture | 4 |
| 16W 277V HID Bollard Lamp by Green Creative | 5 |
| Everest Series Linear High Bay | 6 |
| Slim Wall Pack | 7 |
| Value Flood Series LED Flood Lights | 8 |
| 6in SELECTFIT LED Downlight with 120V-Dimmable by | У |
| Green Creative | 9 |
| Convertaflood LED Flood Lights | 10 |

OW Series Open Face Wall Pack



The OW Series Wall Packs feature a rugged die-cast aluminum housing available in 3 different sizes for a fully scalable solution. The fully gasketed housing is IP65 rated for whole luminaire ingress protection against moisture and environmental contaminants.

- Rugged die-cast aluminum housing
- Bronze polyester powder coat finish
- Custom and factory select colors available
- Non-Cutoff Type IV Distribution
- · Isolated optical compartment with tempered prismatic glass lens and silicone gaskets
- 3000K, 4000K & 5000K CCT Selectable via Integral selector
- Calculated L70 > 100,000 hrs @ 25°C per TM-21-11
- >70 Color Rendering Index (CRI)
- IP65 Rated Luminaire
- 5 Year Warranty (std); 10 Year Warranty Optional

VS New Generation Value Strip LED Fixture



- Architectural design LED Strip fixture
- Steel housing with white powdercoat finish
- 2ft, 4ft, & 8ft lengths available
- Multiple dimming & sensor options to fully control occupied & unoccupied light levels
- Round frosted acrylic lens
- · Ceiling, wall, or suspension mounting options
- Junction box cover included
- 3500K, 4000K & 5000K CCT
- >80 Color Rendering Index (CRI)
- Calculated L70 > 100,000 hrs
- 0-10V Dimmable Driver (100% 10%)
- 120-277V Universal Voltage
- 5 Year Warranty (std); 10 Year Warranty Optional
- UL Listed for Damp Location
- DesignLight Consortium® Premium Qualified Luminaire

16 W 277V HID Bollard Lamp by Green Creative



Features

- 70W HID replacement
- 125W Incandescent replacement
- Exceptional efficacy up to I36LPW
- 3000K / 3500K / 4000K / 5000K CCT
- 230° & 330° omnidirectional beam angle
- Universal voltage 120-277V
- L70 rated lifetime of 50,000 hours
- 5 year limited warranty

Everest Series Linear High Bay



Features

- Versatile 2', 3', & 4' housing delivering 12,000 56,000 lumens
- Slim Profile post painted steel housing for maximum rigidity
- Tool-less Hinged Driver Access
- Impact Resistant and IP5X Rated Lens Options:
- Frosted Acrylic (FRL)
- Clear Polycarbonate (PCL)
- V-Clips for dual point chain or cable hanging (std.)
- Advanced and Basic Controls Options
- -20°F–122°F Ambient Temperature Range
- 4000K-5000K CCT
- >80 Color Rendering Index (CRI)
- Calculated L70 > 100,000 hrs
- 0-10V Dimmable Driver (100%-10%)
- 120-277V Universal Voltage and 347-480V High Voltage via step down transformer
- 5 year warranty (std); 10 year warranty optional
- ETL Listed for Damp Location

Slim Wall Pack



The Slim Wall Pack features a low profile housing and quick mounting bracket for easy installation. It has a Passive Infared (PIR) Sensor, other lighting controls, selectable lumen output and color temperature, plus more ideal exterior qualities. The perfect solution for a broad range of outdoor lighting applications

















Value Flood Series LED Flood Lights



Get Flooded with Energy savings – up to 85% savings compared to HID.

Ultra slim and versatile with five different sizes to choose from, Value flood provides application adaptability for pole mount, wall, or ground installations. Ideal for wall washing/grazing, signage, area lighting, landscape lighting, canopy lighting, and general floodlighting applications.

The Value Flood Series' sleek low-profile designs allow it to discreetly enhance and blend into site surroundings while providing industry leading features and performance. The clear choice for budget friendly flood lights that meet our demanding quality standards and yours.





6in Selectfit LED Downlight



Model No. SLFT6/80CCTS/DIM120V UPC No. 045079985421

Features

- SelectKelvin Technology Choose your CCT
- SelectDrive Technology 3 defined light levels
- High efficacy 105 LPW
- Wet Location, IC and Airtight Rated
- 120V line voltage or 0-10V dimming available
- Deep recessed lightsource, reduced glare
- Universally Compatible with 6□ housings
- For retrofit or new construction installation
- L70 Rated Lifetime of 50,000 Hours
- ETL Listed & ETL Classified

Convertaflood LED Flood Lights



The ILP LED Convertaflood LED flood lights with embedded photocell and push-button convertible top provides toolless access for easily swappable optics, field adjustable output and individual luminaire lumen output control.

Features

- Architectural die-cast aluminum housing
- Embedded photocell with override switch
- Field swappable NEMA optical distributions
- Pushbutton convertible top provides tooless access
- Field Adjustable Output (FAO) allows individual luminaire lumen output control
- Calculated L70 > 100,000 Hours @ 25°C per TM-21-11



About ILP



Since its inception in 2003, ILP has focused its business solely on the manufacturing of energy efficient quality lighting products for both new construction and retrofit, covering a wide variety of commercial, industrial, and outdoor applications.

Headquartered in Sanford, FL, ILP has over 100,000 sq ft of manufacturing, assembly, R&D and customer support to service our growing customer base, which spans the entire U.S., Canada, Central and South America, the Caribbean, and even as far away as American Samoa. These customers include many well-known corporations like Amazon, Apple, AT&T, GM, Proctor & Gamble, 3M, U.S. Gov., Walt Disney World and many more.

With an ongoing commitment to expand and develop, focusing on emerging technologies and innovations, ILP ensures we'll always be "Your number one source for energy efficient lighting!".









Carmel, Indiana Phone: (317) 969-5337